DRAGON POWER ON 1 KVA-3 KVA

-

++++

LBS

The UPS with ECO operation mode that works with high fidelity

TITI



lbspower.com



DRAGON POWER ON 1 KVA- 3 KVA

RACK/TOWER UPS

The Dragon Power ON Series (1-3 KVA) features a design that allows it to be converted to a rack or tower.

It supports economic mode operation (ECO) that makes it more adaptable to your needs. The patented Mimic LCD screen can be rotated by simply pressing the front button. This screen allows monitoring and accessing the status of the UPS, you can also check the estimated time remainig in that space.



Applications



Finance Telecom Energy Medical Government

- Output power factor 0.9
- SNMP Card works with USB or RS-232 together.
- Hot swappable battery.
- Cold start.
- Critical and no critical loads can be configurated.
- Emergency shutdown.
- The frequency converter mode can be configured.







Dragon Power ON (1-3KVA) is available with internal batteries or combined with external battery cabinets for more autonomy.

Ideal to protect:

- Servers
- Banking & Finance
- Medical equipments
- · CCTV
- Industry





SNMP Card



LCD Digital Display moved vertically and horizontally



Digitally Controlled Technology



Rack/ Tower compact design



Smart RS232+ USB+EPO Interface



95.5% AC/AC Efficiency





PECIFICATION CHARACTERISTICS S CHNICAL Ш \vdash

DRAGON POWER ON	1 KVA	1.5 KVA	2 KVA	3 KVA	
	ΙΝΡυΤ				
VOLTAGE (VAC)	80-145 VAC @ Complete Load 70-145 VAC @70%< load ≤ 80% 60-145 VAC @ 60%< load ≤ 70% 55-145 VAC@< load ≤ 60%				
FREQUENCY (HZ)	44Hz-55Hz@50Hz/55-66 Hz@60Hz (auto-detection)				
POWER FACTOR	≥0.99				
THDi	<5%				
PHASE	One Phase with ground				
MAX INPUT CURRENT	13	15	20	29	
INPUT BREAKER REQUIRED	1x15 A	1x20 A	1x30 A	1x32A	
	Ο U T P U T				
VOLTAGE (VAC)	100/110/115/120/127 VAC				
POWER FACTOR	0.9				
VOLTAGE REGULATION	±1%				
CREST	3:1				
FREQUENCY (HZ)	46-54Hz@50Hz/56-64Hz@60 Battery Mode: 50/60 Hz				
THDu	≤3% (linear load) ; ≤5% (no-linear load)				
OVERLOAD CAPACITY	30S @ 100%-150%; 300ms @>150%				
WAVEFORM	Onda Sinusoidal Pura				
	EFFICIENCY				

MODELS

AC MODE	93%					
BATTERY MODE	90%					
ECO MODE	98%					
	BATTERIES					
BATTERY NUMBER/SET	2	3	4	6		
BATTERY TYPE	12V,9Ah					
RECHARGE TIME (TO 90%)	5 hours					
CHARGING CURRENT (MAX)	1.4 A					
BATTERY RATED VOLTAGE	24 VDC	36 VDC	48 VDC	72 VDC		



CHARACTERISTICS	MODELS					
DRAGON POWER ON	1 KVA	1.5 KVA	2 KVA	3 KVA		
	PHYSICAL					
DIMENSION (W*D*H) mm	440 x 430	440 x 430 x 86.5		440x720x86.5		
NET WEIGHT (KG)	13.9	17.8	20.1	23.3		
	INDICATORS					
AUDIBLE ALARM	Battery Mode : Sounding every 4 seconds Low Battery: Sounding every second Overload: Sounding twice each second Fault: Sounding Continously					
	COMMUNICATION					
SMART RS232/USB	External Modbus card supported by RS232,Software supports Windows Family, Linux, FreeBSD					
INTELLIGENT SLOT	Mini SNMP slot (independent to RS232) - Compatible with network card.					
	ENVIRONMENT					
NOISE	<50dB@ 1m					
OPERATION TEMPERATURE	0~40°C					
RELATIVE HUMIDITY	0 ~ 90%, no condensation					
	S T A N D A R D S					
STANDARDS	UL					





Dragon Power ON (Frontal View) Dragon Power ON (Rear View)

LBS POWER

Since its foundation in 2005, LBS is specialized in the production and distribution of UPS and equipment of low and medium voltage for electrical solutions.

Its core business is based on offering excellent products, which allow enormous savings by providing clean energy, respecting the environment and solving mission-critical energy situations for its customers, in addition to provide excellent technical service and 24/7 assistance.



LBS has offices in Mexico and the United States and a production factory in Italy.

Additional Services



Technical Service



Diagnostic Service



Pre sale and Post sale Advice



Preventive and Corrective Maintenance



Energy quality study



LBS Power Technologies

- USA 2385 NW Executive Center Dr Suite 100, Boca Raton, FL. 33431, USA
- & (+1) 772-444-3135
- info@lbspower.com
- www.lbspower.com







Lemonroy Business Solutions

Calzada de la Viga 918 Col. Santa Cruz, CP. 08910, Alcaldía Iztacalco, Ciudad de México

- & (+52) 55-5484-8417 (+52) 55-5554-3907
- ☆ ventas@lemonroy.com
- www.lbspower.com